

for anaologic TTL sistem and manual, for Digital sistem  
cod. 293



Lighting angle: 90°  
Guide Nr.: 38 at 100 ISO in air  
3 power in TTL and 3 in manual  
Pilot lamp of 10/20/35 W  
Anular flash bulb of 4500° Kelvin  
LED battery charge  
LED ready flash  
Electromagnetic switching  
Manual full power: 300 lamps  
Pilot lamp 20 W burn time: 80'  
NiCd batteries  
Automatic battery recharger with computerized control  
Size: 200 mm x Ø 100  
Weight in air: 2.380 Kg  
Weight in water: 0.250 Kg  
Depth: 100 mt

**LBS HOUSING FOR STROBES**  
cod. 393



Size: 220 mm x Ø100  
Weight in air: 1.170 Kg  
Weight in water: -0.100 Kg (positive)

Housing for Nikon flashes: SB24/SB25/SB26/SB28/SB80/SB600/SB800/SB900 and each model with co  
Depth: 150 mt

### VE FOR ALL NIKONOS CONNECTOR ATTACHEMENT



SLAVE L is equipped a micro board that permit to use with any type of UW strobes equipped with a Niko  
Strobes withuot ready to flash on the camera magnifier "pronto flash" in the viewfinder, need to use the m

Type of material: TRANSPARENT PLEXIGLASS

Female bulkead attachement: NIKONOS TYPE

Two pin conatct: MANUAL USE

Depth use: 150 mt

Suggestion to use:

THE FRONT SIDE SLAVE PUTS NEAR TO THE PRINCIPAL STROBES. OR IN FRONT OF THE PHO