

SUPERHANDYLIGHT L300-2 HID 35

ILLUMINATOR WITH HID BULB 35W TO/GAS DISCHARGE with separated battery canister



Technical data

Gas discharge technologie

Power	35W(=alogen bulb about 120W)
Luminosity	3350 lm +/- 300 lm
Burn time	70 minutes with one switching, 60 minutes (with 3 switching)
Battery	NiNh with termic protection total safety

Charge condition: 1000mA for 7 hours (minimum)

2000 mA for 3 hours and half (minimum)

life service 500: recharge cycles (minimum)

Discharge gas valve unidirectional subject periodic maintenance

Depth use 450 feet (on request 750 feet)

Protection termic system stops automatically light if there is overheating. when temper

Mechanical maintenance any 6 months to avoid water inside

Electric maintenance not discharge full battery pack and/or light if unused for long time. Observe
Standard reflecting group 80° diffused with quartz treatment

Battery pack size Diameter 100x100mm (x2, head)

Total weight on surface Kg. 2.270

Underwater weight Kg. 0,200

Surface weight head light Kg. 1,200

Underwater weight head light neutral

Underwater battery weight Kg. 1,220

Accessory under request SADDLE WITH BELT TO FIT BATTERY PACK ON MONO/TWIN TANK,

AUTOMATIC FAST BATTERY CHARGER,
ARMS AND INOX JOINT FOR HEAD LIGHT