



1 - MINIHANDYLIGHT 10-35

cod. 494

Aluminium anticorodal anodized
Tempered glass float type
Depth rating: 490 feet
Waterproof resistance by O rings
Bulb type: alogen G4 6V, 10/20/35 W
Battery pack: NiCd interchangeable and water resistant
Time of charge (std. charge): 6 hours
Time of charge (optional automatic charger): 2 hours
Quartz treated reflecting element
Angle of light: 40° 1mt
Burn time with 10W: 45 min
ON/OFF with electromechanical switching
Size: lenght 158 mm, Ø 56 mm
Weight: 0,620 Kg (on air) - 0,100 Kg (underwater)

2 - HANDYLIGHT 10-35

cod. 495

Power supply: 6V, 3A
Lamps: 10/20/35W
Burn time: 40' (20W)
Weight (in air): 0.7 Kg
Weight (in water): 0.2 Kg
Lenght: 200 mm, Ø 56 mm
The Handylight's reflecting group can be separated and connected by cable to its battery pack or to the

3 -SUPERHANDYLIGHT 10-35

cod. 496

Power supply: 12v, 3A
Lamps: 10/20/35 W
Burn time: 80' (20W)
Weight (on air): 1.2 Kg
Weight (underwater): 0.4 Kg
Lenght: 285 mm, Ø 56 mm
The Handylight's reflecting group can be parted and connected by cable to its battery pack or to the rear

4 - SUPERHANDYLIGHT
10-50

cod. 496 F



Material type	alluminium anticorodal anodized
front glass	tempered float glass
Depth use	150 mt "special type = 250 mt"
waterproof	by o rings
bulbs type	halogen G6 12V, 10/20/35/50 W
replace bulbs	

Unscrew screw and pull out bulbs group of the head
-see picture-



batteries	12V- NiCd, 3A
recharge time	6h / "optional automatic recharge battery 3h"

Low/medium Power Lights (10-50 W)

parabola	quartz
light angle	
	40° at 1 mt.
burn time with bulbs 20 W	80'
ON/OFF	
	with puhbotton electomechanical
size	
	L 300 mm, Ø 56 mm
weight	
	on air 1,200 Kg. / underwater 0,400 Kg.